




Mobile Gateway

LTE-M (Cat-M1)/NB-IoT with BLE, GPS & Wi-Fi Location



Combination tracker and gateway, this mobile gateway can track its location through GPS & Wi-Fi and scan for nearby assets. This allows for high precision indoor & outdoor tracking and managing multi-part assets or systems.





4.25 x 3.39 x 1.18 in (108 x 86 x 30 mm)

Use Cases



High Value Asset Tracking

When used in conjunction with other STG Gateway solutions, the Mobile Gateway can track high value assets off premise and create real time alerts when entering or leaving points or zones of interest.



Multi Sensor Management and Tracking

The Mobile Gateway can track an asset and report critical asset health data from Bluetooth® equipped sensors such as the [T/H Sensor](#). Easily track location, temperature, humidity, compressor vibration, fuel levels - all with a no wire install.

Technical Specifications



Location anywhere through preconfigured cellular chip. No extra costs or installation required.



Bluetooth 5.2 Gateway allows up to 100 tagged assets to be scanned by a single HD Gateway.

Both [Indoor and Outdoor route history](#) and ribbon charts, when indoor environment is equipped with Bluetooth® tags.



Replaceable AA Batteries can provide as much as 7 years of battery life.



Connectivity

| | |
|------------------------|--|
| Cellular Module | Nordic nRF9160 Modem operates on all major global LTE-M and NB-IoT bands Supported LTE bands: LTE-M (Cat-M1): B1, B2, B3, B4, B5, B8, B12, B13, B14, B17, B18, B19, B20, B25, B26, B28, B66 NB-IoT (Cat-NB1/NB2): B1, B2, B3, B4, B5, B8, B12, B13, B17, B19, B20, B25, B26, B28, B66 |
| Bluetooth® 5.2 Gateway | Bluetooth 5.2 gateway reports nearby Bluetooth tags and sensors for affordable tagged asset management and sensor monitoring. Gateway range influenced by sensors used, Gateway location and environmental interference. |

Location

| | |
|-------------------------|--|
| Chipset Environment | Semtech LR1110 |
| GPS/GNSS Scanning | Indoor/Outdoor Concurrent GPS/BeiDou |
| Wi-Fi Location Scanning | Indoor asset location using Wi-Fi access point scanning |
| Cell Tower Location | Cell tower fallback for positioning when there is no GNSS or Wi-Fi signal Asset |
| Cloud-Based Solver | location is calculated in the cloud, not on device, reducing battery consumption |
| *Location Accuracy | ~15 ft -200 ft with GPS/GNSS scanning in open areas ~30 ft - 450 ft with Wi-Fi in urban areas ~800 ft to 1 mile with Cell Tower Geolocation - dependent on number of nearby towers |
| Low Noise Amplifier | GPS signals are filtered and boosted by low-noise amplifier (LNA) allowing operation where other units fail |
| GNSS Assistance | GNSS almanac data for greater sensitivity and position accuracy |

*Results vary based on real world conditions. Device configuration, installation, environmental conditions, augmentation services, and many other factors may lead to variations in positioning accuracy.

Batteries

| | |
|-------------------------|--|
| Replaceable Batteries | 3 x AA Batteries |
| *Battery Life Estimates | Twice Daily Location Updates - 7 Years Daily Updates with Recovery Mode - 4 Years |

* Battery life estimates are influenced by several factors including temperature, installation and orientation of the device, the frequency of location updates, network coverage, sensor integrations, peripherals, accelerometer settings, and more. Battery life calculators are available at support.digitalmatter.com.

Power

| | |
|---------------|------------|
| Input Voltage | 3.0 - 5.5V |
|---------------|------------|

| | |
|---------------|--|
| Sleep Current | <10uA, Average current in lowest power configuration |
|---------------|--|

Mechanics/Design

| | |
|------------|--|
| Dimensions | 4.25 x 3.39 x 1.18 in (108 x 86 x 30 mm) |
|------------|--|

| | |
|--------------|---|
| IP/IK Rating | Ultra-rugged and waterproof IP68 and IK07-rated housing can withstand impact, fine dust, and brief submersion |
|--------------|---|

| | |
|-----------------------|-----------------------------------|
| Operating Temperature | -22° F to 140° F (-30°C to +60°C) |
|-----------------------|-----------------------------------|

| | |
|------------------|----------|
| Cellular Antenna | Internal |
|------------------|----------|

| | |
|-------------|----------|
| GPS Antenna | Internal |
|-------------|----------|

| | |
|---------------|----------|
| Wi-Fi Antenna | Internal |
|---------------|----------|

| | |
|----------------------|---|
| 3-Axis Accelerometer | 3-Axis accelerometer to detect Movement and High-G events |
|----------------------|---|

| | |
|----------------------|---|
| Diagnostic LED Flash | Diagnostic LED indicates operation status |
|----------------------|---|

| | |
|--------|---|
| Memory | Internal flash memory stores approximately 1400 records |
|--------|---|

| | |
|-------------|--|
| Temperature | Reports internal temperature which provides an indication of ambient temperature |
|-------------|--|

Smarts

| | |
|-------------------|---|
| Adaptive Tracking | Customizable location updates and reporting conditions. Movement based, time based and geofence triggers can all influence when a tracker communicates its location. These automated or manual updates can be used to conserve battery life and provide location intelligence exactly when you need it. |
|-------------------|---|

| | |
|-------------------------|---|
| Battery Life Monitoring | 'Battery Low' and 'Battery Critical' alert levels |
|-------------------------|---|

| | |
|-----------------|---|
| Geofence Alerts | QuickTrack platform can use device location to create geofences anywhere and alerts if an asset enters or leaves designated locations |
|-----------------|---|

| | |
|------------------|---|
| Impact Detection | Impact-detection alerts when G-forces are exceeded by a defined threshold |
|------------------|---|

| | |
|---------------------|--|
| Run Hour Monitoring | Capture run hours based on movement to understand and optimize asset utilization |
|---------------------|--|

| | |
|------------------|---|
| Tamper Detection | Optional magnetic switch provides an alert if the device is removed |
|------------------|---|

| | |
|----------------|---|
| Theft Recovery | Automated or manual triggers for "Recovery Mode" to quickly locate off-premise carts with near real time location updates while conserving battery when on premise. |
|----------------|---|

Security

| | |
|---------------|---|
| Data Security | Military-level AES-256 Encryption from device to Device Manager to protect the integrity and confidentiality of telematics data. Data forwarded to QuickTrack software is sent via HTTPS for end-to-end security. |
|---------------|---|